

COMPOSITION AND PROCESS FOR TREATING POLLUTION

Cross Reference to Related Applications

5 This application claims the benefit of U.S. Provisional Application No. 60/217,472 filed July 11, 2000, which is incorporated herein by reference in its entirety.

Field and Overview of the Invention

1 This invention relates to compositions and methods for treating pollutants, and, more particularly for pollution caused by spills of petroleum products.

15 The invention is for a composition and method for the bioremediation and subsequent emulsification of a petroleum product that has been spilled upon a portion of the earth's surface.

20 The composition of the invention is preferably comprised of three basic components. The first component is an assimilable carbon containing composition, preferably one for emulsifying fats and oils, and may contain non-toxic primary surfactants and/or secondary surfactants.

25 This second component comprises a nutrient which is introduced to the hydrophobic carbon containing emulsifying material, which is

the first component.

The third component comprises a compound that is also carbon containing, both non-toxic and non-flammable, and acts as a diluent for the microemulsion, preferably facilitating the safe application of the bioremediation active ingredients (the first and second components) evenly and thoroughly onto the petroleum product contaminant.

Background of the Invention

Technology and industry has relied substantially on the use, by-products and energy, of oil and oil-based products. In fact, this reliance continues to grow, with the result that accidents with oil based products will occur with greater frequency causing oil pollution, sometimes of a serious nature.

Various approaches have been used in combating or remediating oil related pollution. In this regard, the remediation industry has relied primarily on mechanical devices and methods to remove contamination from the affected area. Unfortunately, these methods are not always satisfactory. In certain instances, the mechanical solution results in the pollutant merely being moved off site. In an even worse situation, the pollutant is transferred to another medium, such as the air, through burning. The process by which these mechanical devices "remove" the contaminant can often be as

destructive to the environment as the original pollution itself.

Another approach to pollution cleanup has been through the use of microorganisms. It is known that there exists a well established, highly diverse population of microorganisms that degrade petroleum hydrocarbons. The application or utilization of petroleum degrading microorganisms in spilled oil situations is known generally as the process or method of bioremediation. Bioremediation has been successfully used to treat contaminated soil in above-ground treatment systems, above-ground slurry bioreactors, slurry pits, above-ground soil heaps, composting material, and in situ. A good example showing the use of in situ soil treatment by microorganisms followed the Exxon Valdez oil spill in Prince William Sound, Alaska in 1989. This spilled oil contaminated miles of Alaskan shoreline. An approximately 70 mile section of shoreline was treated using bioremediation techniques. One aspect of the remediation process employed in Prince William Sound focused on enhancing the indigenous microorganisms' growth and oil degrading activities through the application of nutrients (see Roger Prince, et al. 1993 "Bioremediation of the Exxon Valdez Oil Spill: Monitoring Safety and Efficacy," Lewis Publishers; 107-124; 1994).

Unfortunately, there are a number of shortcomings in existing bioremediation technologies. For example, the Inipol technology

advanced by the French contains a stabilizer in amounts that exceed
OSHA exposure limits. This apparently has led to several reported
health claims to the Alaska Worker's Compensation Board (see, for
example, Roberts vs Veco, 1996 Alaska Worker's Compensation Board,
AWCB Case #9034054, AWCB Decision #96-0029), and severely
restricted the product's use.

The exposure limits established by OSHA often in fact prevent
the use of many bioremediation products in enclosed environments,
such as within a plant structure. It is recognized that worker
exposure to bioremediation products may be a far greater health
risk than the hydrocarbon contamination itself. Therefore, within
these areas, standard degreasers substitute as clean up techniques
for the more effective and environmentally sound use of
bioremediation.

Another limitation preventing the widespread use of
bioremediation in active work sites is the flammability issue.
Refineries and terminals, which are key handlers of oil and thus
key sites of hydrocarbon contamination, have strict safety
procedures regulating the use and transportation of flammable
material within active facilities. These regulations are also
followed by DOT, OSHA and other agencies supervising the use of
flammable and combustible products.

[illegible]

20

U.S. Patent No. 4,460,692 (Tellier) discloses a microemulsion made of a nutrient formulation comprising a hydrophobic external phase and an internal water-soluble internal core. The stabilizer package is chosen for its volatility and is listed as butyl ether of ethylene glycol, an undesirable product on the OSHA exposure list.

U.S. Patent No. 3,883,397 (Townsky) discloses a particulate material made of a nutrient formulation coated with a lipophilic material that suspends the material in the oil or near the oil-water interface. This coating is composed of magnesium, aluminum and calcium salts of lipophilic fatty acids, specifically magnesium stearate.

U.S. Patent No. 5,725,885 (Felix) discloses a composition that is broader than either listed in the above patents. The use of oxygen generating materials clearly advances the rate of bioremediation, but compromises the very issues holding the market back from utilizing the process. The toxicity and flammability of peroxide containing compounds is an industrial concern.

U.S. Patent No. 5,384,048 (Hazen) describes an apparatus and a nutrient fluid to stimulate the natural degradation of chlorinated hydrocarbons. Unfortunately, the carbon source, methane, is highly combustible, limiting the commercial use of

Hazen in bioremediation contexts.

Summary of the Invention

According to one aspect of the invention, there is provided a composition for treatment of pollution comprising: a first component comprising a carbon containing substance in an oil phase; a second component comprising a nutrient in a water phase, the second component being formed as an emulsion within the first component; and a third component comprising a diluent added to the first and second components.

^{1st} Preferably, the first component is selected from the group consisting of fatty acids, esters, alcohols and combinations thereof, and the first component may be an alcohol surfactant with the ability to emulsify fats and oils. Preferably, the first component comprises an acid selected from the group consisting of oleic acid, stearic acid and combinations thereof. The oleic acid or stearic acid may be present in the composition in concentrations ranging between about 20% and 50% by weight.

^{2nd} Preferably, the second component comprises a source of nitrogen and/or phosphorus. The nitrogen may be in a non-toxic form and is preferably selected from the group consisting of urea, cyanamide, and combinations thereof. The phosphorus may also be in a non-toxic form and may comprise a phosphate ester.

In a preferred embodiment, the composition further comprises
water.

3rd
5 Preferably, the diluent is present in sufficient amounts so as
to facilitate the even application of the composition to a
pollution area. The diluent may be a carbon containing, non-toxic,
non-flammable stabilizer, and is preferably butyl carbitol [2-(2-
butoxyethoxy)ethanol]. The diluent may be selected so as to
maintain a flashpoint for the composition above 100°C.

In a preferred embodiment, the composition comprises 20 to 50%
by weight carbon, 0 to 30% by weight nitrogen, 0 to 20% by weight
phosphorus. The composition may comprises about 22% by weight
carbon, about 15% by weight nitrogen, about 25% by weight
phosphorus, about 22% by weight diluent and about 18% by weight
water.

According to another aspect of the invention, there is
provided a method of forming composition for treatment of a
20 pollution site, the method comprising: selecting a first component
comprising a carbon containing substance in an oil phase; mixing a
second component with the first component, the second component
comprising a nutrient in a water phase, the second component being
formed as an emulsion within the first component; and diluting the
25 first and second components in a third component comprising a

diluent selected for its ability to facilitate application of the composition to a pollution site.

5 In one form, this invention relates to the use of bioremediation processes having improved environmental soundness and efficiency over existing technologies. While the concept of bioremediation is decades old, many currently available products or components used in bioremediation fail to conform with government environmental standards relating to such factors as, for example, worker exposure, risk assessment within operating facilities, and inherent toxicity. Thus, the existing uses of bioremediation, or "green", technologies are compromised by the presence of products or components that are not themselves "green" or environmentally friendly.

10
15
20
25 This invention, in one aspect, may significantly expand the potential use of bioremediation by focusing on this clear industrial need, and formulates a bioremediation composition which does not have some or many of the undesirable environmental side effects of existing compositions. By conforming to OSHA, DOT, and EPA environmental standards, the bioremediation process of the invention may, for example, be sufficiently safe to take inside industrial facilities. It may be used on the grounds of active refineries, and applied indoors or out without damaging the environment in any way and without exposing workers applying the

material.

The present invention teaches the compositions and methods for the production of a unique, non-toxic, non-flammable, stable microemulsion, consisting of three components which can be distributed by widely used commercial techniques, such as spraying or any other methods for dispersing the emulsion safely and evenly over petroleum materials that have been spilled upon the surface of

the earth. The first component comprising the composition of the invention is any primary non-ionic, fatty acid, ester, or alcohol non-toxic surfactant known to the art for emulsifying fats and oils. The second component comprises a water based nutrient composition to be held in a microemulsion of water in oil for the purpose of culturing microorganisms normally extant or seeded in the spilled petroleum media. The third component is a carbon containing non-toxic, non-flammable stabilizer to dilute the other (active) components of the composition to a viscosity required or optimal for such application.

When this composition is applied to a fuel polluted surface, the outer phase of the emulsion (i.e. the first component) is assimilated and degraded by the microorganisms in the petroleum medium, gradually exposing the nutrient rich water or inner phase of the emulsion (i.e. the second component). The nutrient greatly accelerates the culturation of the microorganisms present and,

therefore, the speed of the bioremediation process

One aspect of the present invention thus teaches the composition and processing methods which result in the safe application of bioremediation materials that promote the growth of petroleum degrading bacteria. The composition is preferably in the form of a microemulsion composed of an outer carbon-containing emulsifying surfactant or surfactants as a lipophilic external phase, and an associated inner fertilizer or nutrient-rich component dissolved in water as distinct, uniform, suspended droplets as a water in oil microemulsion.

The oil or outer portion is preferably a lipophilic, straight-chained carbon source such as oleic or stearic acid. The fertilizer package is preferably nitrogen in the form of water-soluble urea compounds and phosphorous in the form of microbial phosphate compounds.

An important aspect of the invention is the use of biodegradable butyl carbitol [2-(2-butoxyethoxy)ethanol] to dilute and stabilize the micro emulsion, to maintain a flashpoint above 100°C and to ensure that the product is not harmful to humans exposed to the composition of the invention, either through the application process or by working in contiguous areas.

1
2
3
4
5 The composition of the invention is applied to the contaminated areas to initiate microbial development. The preferred dosage is a rate between 4% and 20% by weight of the hydrocarbon contamination, that is, 4 to 20 parts by weight of the bioremediation composition to 80 to 96 parts by weight of the petroleum contaminant. The application can be achieved by any conventional techniques including, but not limited to, spraying, pouring, or physical mixing.

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204
2205
2206
2207
2208
2209
2210
2211
2212
2213
2214
2215
2216
2

to environments requiring bioremediation activities in that it provides a way to efficiently deliver essential nutrients, in an environmentally sound way.

5 Brief Description of the Drawings ✓

Figure 1 is a table showing the components which make up the composition of the invention and some of the preferred embodiments thereof.

10 Detailed Description of the Invention

15 The materials employed in the present invention deliver carbon, nitrogen, and phosphorus to the microorganisms involved in the bioremediation. Nitrogen must be delivered in a substantially non-toxic form such as urea or cyanamide. Phosphorus must be delivered in a substantially non-toxic form such as a phosphate ester. Carbon must be delivered in a substantially non-toxic, nonflammable form such as oleic acid and 2-(2-Butoxyethoxy) ethanol.

20 Further, a portion of the carbon delivered to the system must be in the form of a microemulsion external phase so that microorganisms consume the carbon containing outer phase, gradually exposing and releasing the water, nitrogen and phosphorous nutrients that cultivate and cause rapid growth of the microorganisms, thus greatly speeding and extending the bioremediation process. Delivery of the nutrients within the oil/water interface in this
25 manner ensures the best results by making the necessary culturing

ingredients available for consumption over a longer period of time, thus extending the effectiveness of the bioremediation process over time. This arrangement yields the best results by making the necessary products available for use.

5

The amount of carbon, nitrogen, and phosphorus can be varied in the composition. Thus, compositions may have from about 25 to 50 percent by weight of carbon, from about 0 to 30 percent by weight of nitrogen, and from about 0 to 20 percent by weight of phosphorus. Stabilizers, which comprise the third component of the composition of the invention, may be present in ranges from about 15 to 35 percent. In one preferred embodiment the total carbon is 22% by weight, the total nitrogen is 15% by weight, the total phosphorous is 25% by weight, and the total stabilizer is 22% by weight. Water is present at a concentration of about 18% by weight.

A composition prepared and constituted in accordance with the particulars provided above will preferably result in a composition which is environmentally sound and safe to use. The use of a microemulsion including the described components may allow the expansion of bioremediation technologies into significantly new areas which have hitherto been inaccessible due to the toxicity or other undesirable properties of the components of existing products.

25

Further, the compositions and methods of the invention may provide a cost effective, environmentally superior approach to one of the most basic environmental challenges facing industry today. Of course, many changes and substitutions could be made to the preferred microemulsion without departing from the spirit and scope of the present invention. For example there are many assimilable carbon containing surfactants known to the art that are nontoxic and non-flammable that could be used in the lipophilic outer phase and a host of water soluble fertilizers containing nitrogen and/or phosphorous that could constitute the inner hydrophilic phase. Also, there could be carbon containing non-toxic and non flammable compounds other than ethoxylated esters or alcohols, such as butyl carbitol, that could stabilize and act as a diluent for such a microemulsion.

Table 1 below sets out some of the physical properties of the composite materials and their formulation. The table contains data extracted from "The Condensed Chemical Dictionary, 9th Edition," 1977 VanNostrand Reinhold Co., New York, N.Y.

Table 1

Component	Formula	Toxicity	Flash Point
Oleic Acid	$C_{25}OOH$	Non toxic	372°F
2-(butoxyethoxy) ethanol	$C_4H_9OCH_2CH_2OCH_2CH_2OH$	Non toxic	172°F
Lauryl Phosphate Soln	$C_{22}(PO_4) + H_2O$	Non toxic	
Composite Materials			>200°F*

* Pensky-Martens Closed Tester, ASTM 93

10
9
8
7
6
5
4
3
2
1
The composition, and methods, for the bioremediation and subsequent emulsification of a petroleum product that has been spilled upon a portion of the earth's surface preferably comprise three components which must be present in a unique combination and balance to fulfill the objective of safely applying them to the petroleum medium for rapid degradation and elimination. The first component is carbon-containing and may be based upon any known compound or compounds used for the production of materials for emulsifying fats and oils containing non-toxic primary surfactants and/or secondary surfactants. Such components might be, but are not limited to, fatty acids, esters and alcohols or mixtures thereof, or any combination thereof taken from a long list of such compounds known to the art and used as fertilizers. This first component may also be referred to as the outer or oil phase

20
19
18
17
16
15
14
13
12
11
10
9
8
7
6
5
4
3
2
1
A second component of the invention introduces to the hydrophobic carbon-containing emulsifying material a water based nutrient composition to be held in a microemulsion of water in oil for the purpose of culturing microorganisms normally extant or seeded in the spilled petroleum media. The nutrients consist of a nitrogen source such as urea or ammonium nitrate, sulfate or phosphate, as the source of phosphorous or any combination of thereof. This second component may also be referred to as the inner

or water phase.

feeding of 1st + 2nd phase forming a microemulsion

The water based nutrient material (second component) is introduced into the emulsifying (first component) under high shear to create a microemulsion with distinct homogenous droplets of nutrients dissolved in water, and preferably having a size ranging between about .20 and 400 angstroms. Actual embodiments of such microemulsions may have droplets from 100-200 angstroms with water present at 11%-50% by weight.

The third component of the invention comprises a compound that is also carbon-containing, both non-toxic and non-flammable, and acts as a diluent or stabilizer for the microemulsion to facilitate the safe and effective application of the active first and second components of the bioremediation composition evenly and thoroughly onto the petroleum product contaminant. The introduction of the substantially non-toxic, non-flammable, non-volatile diluent, present in the composition preferably in the range of about 15 to 35% by weight, reduces viscosity of the active ingredients (i.e. first and second components) to less than 200cSt to allow delivery by spray or other dispersion methods.

The first or outer phase component, the assimilable emulsifying composition, provides the first or initial source of carbon for the culturing process; thereafter, the carbon contained

within the spilled petroleum medium itself continues as the carbon reservoir in the bioremediation process. The first component consists of, but is not limited to, fatty acids, esters or alcohols such as oleic or stearic acid, preferably in concentrations ranging between about 20% to 50% by weight. Preferably, the first component, as well as the composite materials, will be non-toxic, as defined by Section 313 Title III of SARA.

The second component, or inner water phase nutrient-rich component, preferably comprises, but is not limited to, urea and a water soluble phosphate. In a preferred embodiment, the end use ratio of carbon in the target media to nitrogen from urea to phosphorous from the phosphate compound will be approximately 120:10:1.

The third component of the composition (also referred to as the diluent) of the invention preferably acts as a stabilizer that maintains the micro emulsion of the active ingredients (i.e. first and second components) in suspension as a pourable and sprayable liquid, and conveniently may have a shelf life of 6 months or more in a 40°F to 100°F environment.

This third component of the composition should preferably be both non-toxic as defined by Section 313 Title III of SARA reporting requirements and non-flammable with a flash point above

the current standard for flammability (100°F). As an example only, the third component may be selected from the ethoxylated alcohols or the like. One such composition, presently preferred in the composition of the invention, is 15%-28% by weight of butyl carbitol.

It will be appreciated that the composite produced by the combination of all three components - namely, emulsifiers, stabilizers and nutrients - can act as additional food sources.

In a preferred embodiment, the first and third components are ones where the carbon source is oleic acid and butyl carbitol [2-(2-butoxyethoxy)ethanol] present in concentrations from, for example, 25%-40% by weight.

Also in a preferred embodiment, the second component is one where the nitrogen source is water soluble urea which may be present in concentrations from about 0%-30% by weight. Further, the phosphorous source is preferably a phosphate ester which may be present as lauryl phosphate in concentrations which may range between about 0% and 20% by weight.

In a further preferred embodiment, the third component, namely, the stabilizer/diluent, comprises butyl carbitol [2-(2-butoxyethoxy)ethanol], which may be present in concentrations of

about 24.5%.

The invention may comprise many different combinations within the scope of the disclosure contained above.

5

The composition may be diluted extensively on site with water. The resultant emulsion is also stable, nontoxic and non-flammable. Dilution could be from 0 to 400% by volume. Dilution would allow for proper distribution of the composition over a wide area to achieve the desired 4-20% by weight of the composition to the pollutants. That is, the less concentrated the pollutant, the greater the dilution in order to achieve a practical method for achieving the desired concentration.